

DS12F
DS15F
DS28F
DS36F
ED50F
ED50Feco

Quick guide

Put your new Wood's dehumidifier to work in just a few minutes!

Wood's

A. Unwrapping and installing the SMF-filter.

1.

Gently remove the dehumidifier from the box. Make sure to that you don't throw away any important objects that are included in the box.

2.

If there is already a filter attached to your dehumidifier, please remove it before installing the SMF-filter.



3.

Take out the filter and the frame from the bag.



4.

Attach the frame to the dehumidifier. Use the foam tape to make the connection tight and the plastic plugs to attach the frame.



5.

Insert the filter in the frame. Put the lid on. If you need to replace an existing filter, lift up the lid and remove the old filter. Insert a new filter and put the lid back.



B. Starting your dehumidifier

1.

Connect the dehumidifier to a power source. **NOTE!** Always use a grounded power source.



2.

The unit has two controls, the hygostat (top) and the fan speed selector (bottom). To switch the unit on, turn the hygostat clock wise until you hear a 'click', the unit starts.



For continuous dehumidifying, turn the hygostat to its maximum value.

Use a hygrometer to monitor the humidity level of the room. When desired humidity level is reached, turn the hygostat counter clock wise until the unit stops.

When the humidity level rises the unit will automatically start again.

Tip!

Recommended humidity level is between 50-60% RH. (RH = relative humidity).

3.

The condensed water is collected in the water tank on the back of the unit. When the bucket is full, the unit automatically shuts off and a red light on the front is illuminated.



4.

To empty the water bucket, gently pull it out and pour out the water. Reinsert the water bucket and make sure that the float is allowed to hang freely inside.



5.

You can also attach a water hose to the machine. This way you don't have to empty the water bucket, the water will be continuously drained.

Attach the hose fitting connection to the machine.

Fasten a water hose to the connection. Use a 1/2 inch water hose.

Lead the water hose to a drainage. Make sure that the water is drained downwards.

As there is no pump in the unit, you must let gravity do the work!



Wood's dehumidifiers are distributed by TES Scandinavia.

If you have any questions, don't hesitate to contact us.

info@tesscandinavia.se

For your closest reseller in your specific country,
please visit www.woodseurope.com

Wood's